



EXTENDER 518

Features

- Specially formulated to enhance the application properties of our premium products without adverse effects on dry film properties
- Proprietary 100% acrylic
- Low VOC
- For interior and exterior use

Recommended For

Use as a wet edge extender for Acrylic and Waterborne interior or exterior coatings. For brushing, rolling or spraying. Residential or commercial applications. Interior or exterior use.

General Description

A premium quality waterborne extender for Benjamin Moore® premium waterborne paints. Use as a thinner and open time extender for premium interior or exterior waterborne products when application conditions require it. Can be used for brushing, rolling or spraying. Especially useful under relatively dry, windy or hot applications conditions

Limitations

- Do not apply when air and surface temperatures are below 4.4 °C (40 °F).

Product Information		Technical data for white	
Standard Colours	Clear	Vehicle Type	Proprietary Acrylic
Tint Bases	NA	Pigment Type	NA
Colorant System	Do not tint	Volume Solids	4.0%
Certifications & Qualifications: VOC compliant in all regulated areas		High humidity and cool temperatures will result in longer dry, recoat and service times.	
Technical Assistance Available in the UK through Benjamin Moore UK showrooms and Authorized Stockists. See www.benjaminmoorepaint.co.uk/stores for contact information. Benjamin Moore corporate customer service +1 855-724-6802 or info@benjaminmoore.com		Dries By Evaporation, Coalescence Viscosity (Zhan 2) 10 – 25 Flash Point None Gloss / Sheen NA Surface Temperature – Min. 4.4 °C (40 °F) at Application – Max. 32.2 °C (90 °F) Clean Up Thinner Clean Water Weight Per 3.79 L 5.4 kg (11.9 lbs.) Storage Temperature – Min. 4.4 °C (40 °F) – Max 32.2 °C (90 °F)	
		Volatile Organic Compounds (VOC) EU Limit - Not Applicable MAX VOC 0.1 g/L	

Extender (518)

Surface Preparation

Surfaces must be clean and free of grease, wax, and mildew. Remove any chalk and loose or scaling paint. Glossy surfaces must be dulled. Un-weathered areas such as eaves, ceilings, and overhangs should be washed with a detergent solution and/or rinsed with a strong stream of water from a garden hose to remove contaminants that can interfere with proper adhesion. Mildew must be removed by application of a commercial mildew wash. Caution: Use rubber gloves, work goggles, and protective clothing. For metal surfaces, remove rust. Wipe down with paint thinner to remove surface oils.

Application

This product is designed to be used as an extender for interior and exterior waterborne Finishes. This product is not designed to be used alone. Mix a maximum of 236 mL to a 3.79 L can of waterborne paint.

Do not mix this product with alkyd or oil based coatings.

Thinning/Clean Up

Clean Up: Wash painting tools in warm soapy water immediately after use. Spray equipment should be given a final rinse with mineral spirits to prevent rusting.

WARNING Contains 2-Methyl-4-isothiazolin-3-one



Hazard statements

H317 - May cause an allergic skin reaction

Precautionary Statements - EU (§28, 1272/2008)

P101 - If medical advice is needed, have product container or label at hand. P102 - Keep out of reach of children. P261 - Avoid breathing dust/fume/gas/mist/vapors/spray. P280 - Wear protective gloves. P303 + P361 + P353 - IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water. P501 - Dispose of contents/ container to an approved waste disposal plant.

FIRST AID: In case of eye contact, flush immediately with plenty of water for at least 15 minutes; for skin, wash thoroughly with soap and water. If symptoms persist, seek medical attention. If you experience difficulty breathing, leave the area to obtain fresh air. If continued difficulty is experienced, get medical attention immediately.

IN CASE OF SPILL – Absorb with inert material and dispose of as specified under **Thinning/Clean up**.

PROTECT FROM FREEZING